LG SERIES COMPACT EFFICIENT HOSE & TUBING REELS



LG SERIES .: REEL SPECIFICATIONS

SWIVEL • Externa full-flo • Swivel DESIGN & • Compa & facility

- · External fluid path with machined from solid brass 90°
- full-flow NPT swivel inlet

Swivel Seals: NITRILE

- DESIGN & STRUCTURE
- Compact & lightweight spring driven hose reel save space & facilitate workplace organization
- CoxComposite™ grommet with continuous radius design that does not pinch or catch the hose during operation
- Solid one piece, 12GA steel base & support post for maximum stability
- Designed for lightweight PVC hose & tubing

RETRACTION

- Enclosed factory tuned & matched cartridge-style spring motor
- Non-corrosive CoxComposite™ ratchet hub with self lubricating bronze bearings secures hose at desired length

SIGNATURE FEATURES

- · Professional grade heavy duty steel construction
- Durable proprietary CPC[™] powder coat process
- Rolled edges & ribbed discs provide strength & safety
- Leading 2-year manufacturer's limited warranty
- Made in the U.S.A. Sold & Supported Worldwide

POSSIBLE FIELDS OF APPLICATION

- Pneumatic Tools
- Tubing Applications
- Washdown
- General Commercial & Industrial
- Bench Mount

Service / Mechanic / Utility Vehicles

Machine ShopsMaintenance, Repair &

Operations

ACCESSORIZE YOUR REEL :: PG 50

O-Rings & Swivels

Assorted Reel Accessories

COXREELS® LG Series "Little Giant" is the first lightweight - heavy duty reel on

the market. The LG is perfect for commercial or industrial applications where space or budget is limited. It is extremely lightweight and compact and can install almost anywhere. This little giant can accept either a 1/4" or 3/8" hose to tackle the jobs of reels almost double its size.


LOW PRESSURE

Models with hose are for air or water service with a maximum temperature 150° F. Models less hose can be used for air, water or oil. Note: Do not exceed listed hose 0.D. to obtain maximum length.

-											
	LESS HOSE		SIZE								
MODEL	I.D.	0.D.	FT.	PSI	APRX. LBS.	MODEL	APRX. LBS.	INDEX			
LG-LP-115	1⁄4"	1⁄2"	15	300	9	LG-LPL-115	8	1			
LG-LP-125	1⁄4"	1⁄2"	25	300	11	LG-LPL-125	8	1			
LG-LP-310	3⁄8"	5⁄8"	10	300	9	LG-LPL-310	8	1			
LG-LP-320	3⁄8"	5⁄8"	20	300	11	LG-LPL-320	8	1			

REEL DIMENSIONS Technical Data Sheets Available On Website

SIZE INDEX	W	H	L	Х	Y	М	Ν
1	5 ¹ /4"	105⁄8"	101⁄2"	4 ¹¹ ⁄16"	83⁄8"	21⁄2"	6"
	(verall Dimensions		Ra	0.0	Mounting Pattern	



COXREELS® LG FEATURES

CoxComposite™ Hub Features

- Integrates High-Strength Composite With Self Lubricating Bronze Bearing
 Over 100% More Impact Strength Than Typical Glass Filled Polypropylene
- Used In Other Reels
- Strength Actually Increases By 20% At Sub-Zero Temperatures
- (Actual Test Results Measured At -40°C)
- Excellent Chemical Resistance

COXREELS® LG FEATURES



CoxComposite™ Grommet Features

- Continuous Radius Design Allows The Use Of Various Size Tubing In Addition To Standard Hose Sizes
- · Absolutely No Pinching & No Place To Catch
- Bearing Grade, FDA-Compliant Composite
- Excellent Chemical Resistance

