BOTTLE JACKS

Low Profile 12, 20 & 30 Ton



THE RIGHT CHOICE FOR THOSE LOWER CLEARANCE JOBS.

- All the quality, features and lifting capacity of the standard jacks in short form. The 12-ton and 20-ton models feature screw extensions for added versatility.
- All jacks meet ASME B30.1 standards and carry the Power Team Powerthon[™] Lifetime Warranty.
- All jacks operate both vertically and horizontally for use in a variety of lifting, pushing and spreading applications.



					ORE	DERING IN	FORMAT	ION*				
			Retracted Height			No. Pump Strokes to	Saddle		Pump Handle	Handle Effort at		Product
Cap.	Stroke	Order	Min.	Ext.	Ext.	Ext. Piston	Dia.	Base Size	Length	Rated Cap.	Carry	Weight
Tons	(in.)	Number	(in.)	(in.)	(in.)	(in.)	(in.)	(in.)	(in.)	(lbs.)	Handle	(lbs.)
12	3 ³ / ₄	9012A	6 ³ / ₄	3	13 ¹ / ₂	26	1 ⁷ /8	6 ¹ / ₂ x 4 ³ / ₁₆	23 ¹³ / ₁₆	60	Yes	14
20	3 ³/8	9020A	7 ¹ / ₈	1 ⁹ / ₁₆	12	22	2	7 ³ / ₁₆ x 5 ¹ / ₁₆	31 ¹ / ₂	70	Yes	22.2
30	3 ¹ /8	9130A	7 ¹ /8		10 ¹ / ₄	35	2 ³ /8	7 ⁹ /16 x 5 ⁹ /16	39³/8	50	Yes	30.2

‡ 2 Speed: Rapid advance≈40 strokes; Lift mode≈160 strokes.