

SIDEWINDER JACKS

Mini Jacks

5-20 Ton



COMPACT SIDEWINDER MINI JACK FITS IN YOUR PALM AND DELIVERS 5, 10 & 20 TONS OF LIFTING FORCE.

Meets ASME B30.1 standard



- Retracted height of just 2⁹/₁₆" for the smallest jack and 5¹/₈" for the 20 ton, allows you to slip this jack into the narrowest of crevices.
- The perfect addition to any toolbox, this remarkable little jack has multiple uses that are limited only by your imagination. Use it as a jack or a spreader. Use it to turn your mechanical gear puller (puller capacity must match jack capacity) into a hydraulic puller. Use it vertically or horizontally in limited clearance situations.
- Jacks operate either horizontally or vertically. Handles function in line with base for easier use in confined spaces.



ORDERING INFORMATION*

Order Number	(in.)	Stroke Number	Retracted		No. Pump Strokes to Ext. Piston	Saddle Dia. (in.)	Base Size (in.)	Pump Handle	Handle	Product Weight (lbs.)	
			Min. (in.)	Max Height (in.)				Length (in.)	Effort at Rated Cap. (lbs.)		Carry Handle
9105A	5	¾	2½	3⅜	30	1⅞ ₆₄	2 ²⁹ ₃₂ Dia.	9 ⁷ ₁₆	57	No	4.2
9205A	5	1½	3½	5⅛	38	1⅞ ₆₄	2 ²⁹ ₃₂ Dia.	9 ⁷ ₁₆	57	No	5.3
9210A	10	1 ³ ₁₆	4¾	5 ⁷ ₈	36	1 ²¹ ₃₂	4 ²¹ ₆₄ Dia.	17 ²¹ ₆₄	62	No	12.1
9220A	20	1 ³ ₁₆	5⅛	6 ⁵ ₁₆	46	2 ⁵ ₆₄	4 ²³ ₃₂ Dia.	23 ¹³ ₁₆	77	No	17.6

*See current price list for shipping weights.