

PIPE FLANGE

Hydraulic Spreaders

5 & 10 Ton



HFS3A

- You'll never again have to resort to "hammer and chisel" methods that waste time and effort. Flange spreaders should be used in pairs to provide even spreading force.
- Standard 60° wedge is suitable for most flanges; 30° "thin" and 60° "blunt" wedges are optional.
- The HFS3A is designed for applications where total thickness of flanges and max. spread gap is 3" or less and flange bolts are a min. of 1/16" dia.
- Use HFS6A if total thickness of flanges and max. spread gap is 6" or less, and flange bolts are a min. of 3/16" dia.



350823



350822



350549



350550

Capacity (tons)	Order Number	Standard Wedge Type	Optional Wedges		Min. Flange Opening			Max. Flange Opening			Min. Combined Flange Opening	Pin Dia. (in.)	Weight (lbs.)
			30° Thin	60° Blunt	60° Std.	60° Blunt	30°	60° Std.	60° Blunt	30°			
5	HFS3A	60° Sharp	350823	350822	1/16"	1"	1/16"	1 1/4"	1 1/4"	23/32"	3 1/2"	1 1/16"	9.0
10	HFS6A	60° Sharp	350549	350550	1/16"	1 1/2"	1/16"	2"	2"	31/32"	6 9/16"	1 3/16"	18.0