PUNCHES PUNCHES

20 & 35 Ton



- Punch smooth, precise holes in seconds; much faster than drilling.
- Fully portable for construction, maintenance and service applications, or can be mounted on a workbench for production jobs. Has carrying handle for precise locating.
- Rugged, forged steel "C" frame for great strength and durability.
- Dual action, spring loaded stripper holds material during punching operation, strips material from punch on return. Scribe lines on stripper aid in locating the punch (HP 35 only).

- Double Acting prevents binding and speeds retraction (HP20 only).
- The PE172 electric/hydraulic pump is an ideal power source.

No. HP35 – Punch only, includes metal case and die change tools. Wt., 42.5 lbs.


No. HP35S – Punch with punches and dies. Includes HP35 punch, metal case and 250459 punch/die set. Wt., 44.0 lbs.

No. HP35P – Punch set with pump. Same as HP35SP, but does not include punch/die set. Wt., 86.3 lbs. NOTE: Available in 220 volt, 50 Hz. Order with suffix "-220".

No. HP35SP – Punch set with pump. Includes HP35 punch, PE172 electric/hydraulic pump, 9756 hose, 9798 hose half coupler, 250459 punch/die set, metal case. Wt., 87.8 lbs. NOTE: 220 volt, 50 Hz. Order with suffix "-220".

No. 250459 – Punch/die set for round holes. Includes one each: PD437 ⁷/₁₆" punch/die, PD562 ⁹/₁₆" punch/die, PD688 ¹¹/₁₆" punch/die, PD812 ¹²/₁₆" punch/die. Wt., 1.5 lbs.





		Max.		Mtng. Max. Throa Max. Holes Depth																
Сар		Oper. Press.		Material Thickness	A (in.)			D (in.)			G (in.)	H (in.)	J (in.)	K (in.)	L (in.)	M (in.)	N (in.)	O (in.)	P (in.)	Q (in.)
35	HP35	10,000 psi	4.6 cu.in.	1/2	13³/₄	9	33/4	9/16	27/8	1/4	3	1 13/ ₁₆	_	213/16	21/4	11/2	31/2	⁷ / ₈	4	³ / ₄

No. HP20 - Basic punch. Wt., 33 lbs.

No. HP20S - Punch frame with cylinder, valve, handle, two coupling nuts, plus five punch and die sets in 1/4", 5/16", 3/8", 7/16", and 17/32" dia. Wt., 35.0 lbs.

No. HP20SP* - Complete punch set with PE102A pump (115V, 50/60 Hz), 9682 nipple, two 9792 female couplers and two 9793 male couplers. Also includes two 9758 10' hoses, 9680 coupling, and same punch and die sets as in HP20S (above). Tool is completely assembled and pre-filled with oil. In storage box. Wt., 83.0 lbs.





Punch Set HP20SP Includes the PE102A pump, hoses, couplers, punch and die sets in sizes 1/4", 5/16", 3/8", 7/16", and ¹⁷/₃₂" diameter, with storage box.

HP₂0



		IYPIGAL ZU IUN ƏIYLE IUULING
PUNCH/DIE SETS FOR HP20 & HP35 HYI		
For use with HP20	For use with	
Hydraulic Punch	HP35 Hyd. Punch	
Punch Punch Flat Die Bevel Couplin	Punch/w Flat Punch/w	INCHES MM

	F	lydrauli	c Punch	1								
Punch	Punch	Punch	Punch Flat Die Bevel		Coupling	Punch/w Flat	Punch/w	Punch	INC	HES	MM	
Size (in.)	Style	No.	No.	Die No.	Nut No.	Die Set	Bevel Die Set		Hole Dia.	Bolt	Hole Dia.	Bolt
1/4		251970	251983		252001			1/4	1/4	#10	6.3	_
5/16		251971	251984		252001	PD313		⁵ / ₁₆	5/16	1/4	7.9	_
3/8		251972	251985	251996	252001	PD375	PD375B	3/8	3/8	5/16	9.5	M8
7/16		251973	251986	251997	252001	PD437	PD437B	⁷ / ₁₆	7/16	3/8	11.2	M10
17/32	Round	251974	251987	251998	252001	PD531	PD531B	17/32	17/32	7/16	13.5	M12
9/16		251975	251988	251999	252001	PD562	PD562B	⁹ /16	9/16	1/2	14.3	_
11/16		251976	251989		252001	PD688		11/16	11/16	5/8	17.5	M16
25/32		251977	251990		252002	PD781		²⁵ /32	²⁵ /32	_	19.8	M18
13/16		251978	251991		252002	PD812		13/16	13/16	3/4	20.6	_
1/2		251979	251992		252002							
17/32	Square	251980	251993		252002							





251981 251994

3/8 x 3/4 Obround 251982 251995

252002

252002

ACCESSORIES FOR HP20 HYDRAULIC PUNCH

No. HP20FS - Optional foot switch mounted in foot switch guard. Supplied with 10 foot cord and male remote connector. Wt., 2.0 lbs.

No. HP20HS - Optional handswitch. Supplied with 10 foot cord and male remote connector. Wt., 2.0 lbs.

No. 252000 - Optional coupling nut wrench. Makes punch/die changes easier without "rounding-off" coupling nuts. Wt., 0.5 lbs.

