AIR PUMP


Hydraulic PA6 Series

Single-Acting


COMPACT, LIGHTWEIGHT AND PORTABLE. SINGLE-SPEED PUMPS DESIGNED TO DRIVE SINGLE-ACTING CYLINDERS.


- The power unit of choice for major manufacturers of auto body, frame straighteners and other equipment.
- Operate at 40-100 psi shop air pressure at the pump.
- dBA 85 at 10,000 psi.
- Serviceable pump motor is not a "throw away," providing economical repair.
- Permanently vented reservoir cap.
- Internal relief valve protects circuit components, air inlet filter protects motor.












Pump No.	A (in.)	B (in.)	C (in.)	D (in.)	E (in.)	G (in.)
PA6	73/4	57/ ₈	4 ³ / ₈	91/2	5	4 x 9
PA6A	73/4	5 ⁷ / ₈	43/8	91/2	5	4 x 9
PA6AM	73/4	5 ⁷ / ₈	4 ³ / ₈	91/2	5	4 x 9
PA6M	73/4	5 ⁷ / ₈	4 ³ / ₈	91/2	5	4 x 9
PA6R	73/4	57/ ₈	4 ³ / ₈	91/2	5	4 x 9
PA6RM	73/4	5 ⁷ / ₈	4 ³ / ₈	91/2	5	4 x 9
PA6M-1	7 ⁷ / ₈	6	4 ³ / ₈	12 ⁵ / ₈	7³/ ₈	_
PA6-2	101/4	8	7	111/2	91/2	5 ¹ / ₈ x 7 ¹ / ₈
PA6M-2	10	73/4	6 ³ / ₄	111/2	91/2	8 x 10









	Order No.	Air Supply Req'd (psi)	Reservoir			
Description			Cap. (cu. in.)	Usable (cu. in.)	Oil Port (in)	Prod. Wt. (lbs.)
Base model pump with high density polyethylene reservoir.	PA6	40-120	105	98	³/ ₈ NPTF	14
PA6 with externally adjustable relief valve.	PA6A	40-120	105	98	³/ ₈ NPTF	15
PA6A with metal reservoir.	PA6AM	40-120	105	98	³/ ₈ NPTF	17
PA6, except has metal reservoir.	PA6M	40-120	105	98	³ / ₈ NPTF	18
PA6 with 12 foot remote control.	PA6R	40-120	105	98	³/ ₈ NPTF	20.58
PA6R, except has metal reservoir.	PA6RM	40-120	105	98	³/ ₈ NPTF	21.58
PA6, except has 1 gallon metal reservoir.	PA6M-1	40-120	1 gal.	185	³ / ₈ NPTF	23.7
PA6, except has 2 gallon, high density polyethylene reservoir.	PA6-2	40-120	2 gal.	454	³/ ₈ NPTF	24.5
PA6, except has 21/2 gallon metal reservoir.	PA6M-2	40-120	21/ ₂ gal.	570	³/ ₈ NPTF	32.1