
ELECTRIC PUMP

Hydraulic PQ60 Series

Up to 200 ton 60 cu. in./min.





PUMP DESIGNED SPECIFICALLY FOR HEAVY DUTY, EXTENDED CYCLE OPERATION.

- For operating single or double-acting cylinders.
- Metal shroud keeps dirt and moisture out of motor and electrical components.
- Electrical shut-down feature prevents unintentional restarting of motor following an electrical service interruption.
- Internal relief valve limits pressure to 10,000 psi. External relief valve is adjustable from 1,000 to 10,000 psi.
- Pumps operate below maximum OSHA noise limitation (74-76 dBA).
- Start and operate under full load, even with voltage reduced by 10%.



PQ603

Prod. Wt.

w/Oil

(lbs.)

169**

Hydraulic Machine Press Operation.



Max. dBa at Pressure Idle and Amp Draw at Oil Del. (cu. in./min. @) Pump Output 10,000 10,000 psi 100 1,000 5,000 10,000 (115 V.)** (psi) (psi) No. (psi) (psi) (psi) (psi) rpm

PQ60 10,000 1,725 74/76* See Chart 730 **Series** (following page)

A B C D E F G H J K (in.) (in.) (in.) (in.) (in.) (in.) (in.) (in.)

 $25^{1}/_{8}\ 14^{1}/_{4}\ 15^{1}/_{2}\ 7^{1}/_{4}\ 12^{1}/_{8}\ 13^{5}\!/_{16}\ 14^{11}\!/_{16}\ 9^{5}\!/_{16}\ 4^{13}\!/_{16}\ ^{1}\!/_{2}-20$ UNF

- * Measured at a 3 ft. distance, all sides.
- ** Total weight with oil and 3-way solenoid valve. Subtract 10 lbs. to obtain weight of pump with manual valve.

65

*** For 2" dia. swivel casters, order (4) No. 10494.









For use with Cyl. Type	Description	Order No.	Valve Type	Valve No.	Valve Function	Max. Amp Draw @ 10,000 (psi)	Motor	Reservoir Usable (cu. in.)
Single-Acting	2 hp pump with 5.7 gal. reservoir and manual valve,	PQ603	3-Way	9520*	Advance Hold Return	115V - 22 amps 230V - 11 amps	2 hp, 230 Volt 60 Hztt, Single Phase	1,250
Single-Acting	PQ603, except has solenoid operated remote valve.	PQ603S	3-Way	9599†	Advance Hold Return	115V - 22 amps 230V - 11 amps	2 hp, 230 Volt 60 Hz++, Single Phase	1,250
Double-Acting	2 hp pump with 5.7 gal. reservoir and manual valve.	PQ604	4-Way	9506*	Advance Hold Return	115V - 22 amps 230V - 11 amps	2 hp, 230 Volt 60 Hztt, Single Phase	1,250
Double-Acting	PQ604, except has solenoid operated remote valve.	PQ604S	4-Way	9512†	Advance Hold Return	115V - 22 amps 230V - 11 amps	2 hp, 230 Volt 60 Hztt, Single Phase	1,250

- * Manual valve. Pump is equipped with RUN/OFF/PULSE switch for control of motor.
- † Solenoid valve. Pump is equipped with a remote control switch with 10 ft. cord.
- th PQ60 series also available in 115V, 60 Hz or 220V, 50 Hz. Please specify when ordering. Example: for 60 Hz order PQ603-115; for 50 Hz order PQ603-50-220.
- Some Power Team pumps are available in special configurations not listed in this catalog. For your special requirements please consult your local distributor or the Power Team factory.