CRIMPING PUMP

Electric PE-Nut

30 cu. in./min Two-Speed

EXTREMELY DURABLE YET LIGHT-WEIGHT AND OPERATE UNDER LOW-LINE VOLTAGE CONDITIONS.

PE-NUT PUMP — 115V

- 5/8 hp universal electric motor (50/60 Hz cycle).
- Two-stage pump for rapid ram advance.
- Operational under low-line voltage conditions.
- Optional operating pressures available; consult Power Team for details.

- Designed for use with spring-returned remote tools.
- · High-pressure safety relief valve.
- Remote hand control with 10-foot cord.
- · Carrying handle.
- · Factory filled oil reservoir.
- · Pressure matched quick-coupler supplied.
- · Optional carrying case.
- · Unique, intermittent duty pump.
- Piston-type high-pressure pump supercharged by a low-pressure pump.





Order No.	Oil Deliver (cu. in./min.)	Oil Reservoir (cu. in.)	Usable Oil (cu. in.)	Overall Width (in.)	Overall Length (in.)	Overall Depth (in.)	Pump Weight w/Oil (lbs.)	
PE-NUT PE-NUTC*	(160 in³ @ 100 psi 30 in³ @ 10,000 psi	93 in ³	43 in ³	6.5	14.38	8.25	28	
*Includes C	ase				Electrical Data	a		
			Electric Motor			Electrical Control		
			5/8 hp, 10,000 rpm			Remote cor	Remote control with 10-foot cord	

115V AC, 50/60 Hz 11 amp current draw (115V @ 10,000 PSI)