

WORLDWIDE MOTOR CONTROLS

Across-Line Motor Starters - Discount Code: MC2

Definite Purpose Motor Starters



Product Overview

- NEMA 1 enclosure
- Door mounted reset PB standard
- Knockouts for field kits
- Control terminals for field ease
- Large enclosure for wire bends
- Field kits for local start / stop
- Field kits for HOA operation
- 24 VAC and 208 VAC control coil available
- Reset pushbutton supplied standard

ACROSS-LINE
MOTOR STARTERS

HP Rating	Main Voltage	Overload Current Setting	Motor FLA	Auxiliary Contacts	Coil Size	Dimensions (Inches) H x W x D	Box Size	With Main Voltage Coil *		With 120 Volt Coil *	
								Model Number	List Price	Model Number	List Price
Three-Phase - 230 Volt											
1	230	4-6	4.2	1NO+1NC	C1	10 x 6 x 4.63	A	WWS1-230		WWS1-230-120C	
1.5	230	5-8	6	1NO+1NC	C1	10 x 6 x 4.63	A	WWS 1.5-230		WWS1.5-230-120C	
2	230	6-9	6.8	1NO+1NC	C1	10 x 6 x 4.63	A	WWS 2-230		WWS2-230-120C	
3	230	7-10	9.6	1NO+1NC	C1	10 x 6 x 4.63	A	WWS 3-230		WWS3-230-120C	
5	230	12-18	15.2	1NO+1NC	C1	10 x 6 x 4.63	A	WWS 5-230		WWS5-230-120C	
7 ½	230	18-25	22	1NO+1NC	C1	10 x 6 x 4.63	A	WWS 7.5-230		WWS7.5-230-120C	
10	230	22-32	28	1NO+1NC	C1	10 x 6 x 4.63	A	WWS 10-230		WWS10-230-120C	
15	230	34-50	42	2NO+2NC	C3	13.25 x 7.38 x 6.13	B	WWS 15-230		WWS15-230-120C	
20	230	45-65	54	2NO+2NC	C3	13.25 x 7.38 x 6.13	B	WWS 20-230		WWS20-230-120C	
25	230	54-75	68	2NO+2NC	C4	20.25 x 8.75 x 7.31	C	WWS 25-230		WWS25-230-120C	
30	230	70-95	80	2NO+2NC	C4	20.25 x 8.75 x 7.31	C	WWS 30-230		WWS30-230-120C	
40	230	95-130	104	2NO+2NC	C4	20.25 x 8.75 x 7.31	C	WWS40-230		WWS40-230-120C	
50	230	110-150	130	2NO+2NC	C5	20.25 x 8.75 x 7.31	C	WWS50-230		WWS50-230-120C	
Three-Phase - 480 Volt											
1	480	1.6-2.5	2.1	1NO+1NC	C1	10 x 6 x 4.63	A	WWS1-480		WWS1-480-120C	
2	480	2.5-4	3.4	1NO+1NC	C1	10 x 6 x 4.63	A	WWS2-480		WWS2-480-120C	
3	480	4-6	4.8	1NO+1NC	C1	10 x 6 x 4.63	A	WWS3-480		WWS3-480-120C	
5	480	6-9	7.6	1NO+1NC	C1	10 x 6 x 4.63	A	WWS5-480		WWS5-480-120C	
7 ½	480	9-13	11	1NO+1NC	C1	10 x 6 x 4.63	A	WWS7.5-480		WWS7.5-480-120C	
10	480	12-18	14	1NO+1NC	C1	10 x 6 x 4.63	A	WWS10-480		WWS10-480-120C	
15	480	18-25	21	1NO+1NC	C1	10 x 6 x 4.63	A	WWS15-480		WWS15-480-120C	
20	480	22-32	27	2NO+2NC	C2	10 x 6 x 4.63	A	WWS20-480		WWS20-480-120C	
25	480	28-40	34	2NO+2NC	C2	10 x 6 x 4.63	A	WWS25-480		WWS25-480-120C	
30	480	34-50	40	2NO+2NC	C3	13.25 x 7.38 x 6.13	B	WWS30-480		WWS30-480-120C	
40	480	45-65	52	2NO+2NC	C3	13.25 x 7.38 x 6.13	B	WWS40-480		WWS40-480-120C	
50	480	54-75	65	2NO+2NC	C4	20.25 x 8.75 x 7.31	C	WWS50-480		WWS50-480-120C	
60	480	63-85	77	2NO+2NC	C4	20.25 x 8.75 x 7.31	C	WWS60-480		WWS60-480-120C	
75	480	80-100	96	2NO+2NC	C4	20.25 x 8.75 x 7.31	C	WWS75-480		WWS75-480-120C	
100	480	110-150	124	2NO+2NC	C5	20.25 x 8.75 x 7.31	C	WWS100-480		WWS100-480-120C	

