

## MANUALLY OPERATED DIRECTIONAL VALVE HD-G06 SERIES

---



### FEATURES

This industrial hydraulic four-way valve is actuated manually with the hand-lever. It may be ordered as a 2-position or a 3-position valve. Other options include a spring-offset or spring-centered design.

The valve mounts on the M06 Subplate series.

Note: Modular pressure and flow control valves in the M\*\*-06 series that mount under this directional control are available separately to make a convenient control valve package.

---

## HD – G 06 – 2 B2 – \*\*

1 2 3 4 5 6

### 1 Series

**HD:** Manually Operated  
Directional Control  
Valve

### 2 Mounting Style

**G:** Subplate Mounted

### 3 Body Style

**06:** Interface 06  
NFPA D08 Size / ISO 4401-08  
/ CETOP 8 / NG 25





### 4 Valve Positions





**2:** Two Position Valve  
**3:** Three Position Valve



### 5 Spool



**Spool Type:** See Chart

### 6 Design Number

4 Way 3 Position Spring Centered	
3C2	
3C3	
3C4	
3C6	

4-Way 3-Position Detent	
3D2	
3D3	
3D4	
3D6	

4-Way 2-Position Spring Offset	
2B2 Closed Crossover	
2B3 Open Crossover	

4-Way 2-Position Detent	
2D2 Closed Crossover	
2D3 Open Crossover	

# MANUALLY OPERATED DIRECTIONAL VALVE HD-G04 SERIES

## Dimensions

HD - G06- \*\*\* - \*\*

MOUNTING SURFACE: ISO 4401-AB-03-4-A

UNIT: mm( inch)

### ● HD-G06

Mounting: NFPA D08

in (mm)

