Transfer Pumps

Order No. Prodcut Weight Description

TO SEE OUR FULL LINE OF DRAWINGS, GO TO WWW.AMERICANMOBILEPOWER.COM

Order No.	Floucut Weight	Bescription	
HP-100	14#	Petroleum Hand Pump The Hand Pump is compatible with a wide variety of petroleum products and fits any container with a 2" NPT bung and tapered threads. Lightweight, die-cast aluminum housing. Stainless steel piston shaft and lir Built-in, anti-siphon valve to prevent leaks. • Pumping Capacity: Up to ½ gallon or 1.9 liters/stroke cycle. • ½ gallon setting for high volume, high resistance; • ¼ gallon setting for low volume, low resistance. • Inlet: 1" NPT Outlet: ¾" NPT • Hose: ¾" x 8 ft. Dry Prime: 5 ft. minimum • Nozzle: Thermoplastic unleaded nozzle. Built-in nozzle holder. • Suction Pipe: Plastic, adjustable 22 to 40 inches • Security: Handle can be padlocked.	
M-150	23#	Standard Volt Electric Pump Application for low viscosity petroleum fuels such as gasoline, kerosene, and diesel fuel. Outdoor, year-round operating use with a temperature range of -20° to +125° F. Designed for mounting on portable, vented storage tanks. Lightweight, corrosion-resistant, cast aluminum body. Convenient spin collar for easy installation. • Pump Rate: Up to 15 GPM • Duty Cycle: 30 min. on/30 min. off • Input: 12 volt DC Motor: 1900 rpm Motor • Protector: 20 amps • Cord: 15 ft. of 12 gauge • Bung: 2" NPT • Inlet: 1" NPT • Outlet: ¾" NPT • Outlet: ¾" NPT • Hose: ¾" x 12 ft. Buna-N • Suction: Plastic, adjustable 22 to 40 inches • Security: Nozzle can be padlocked. Also available with automatic shutoff.	

Transfer Accessories and Parts

TO SEE OUR FULL LINE OF DRAWINGS, GO TO WWW.AMERICANMOBILEPOWER.COM

Order No.	Prodcut Weight	Description	
01A3AGM	1#	Electric Digital Fuel Meter Designed for outdoor, year-round use on fuel transfer pumps in the 3 to 30 GPM (10 to 100 LPM) flow range. Calibrated at the factory for use with gasoline, diesel fuel or kerosene. Requires two AA batteries that can easily be replaced by the user. Approximate battery life is 9,000 hours. Installs easily to the above Electric pump, M-150, for maximum efficiency.	ENGLISHED TO SERVICE OF THE PARTY OF THE PAR
APP-0750-M	1#	Magnetic Port Plug, ¾" NPT	

TO SEE OUR FULL LINE OF DRAWINGS, GO TO WWW.AMERICANMOBILEPOWER.COM

Order No.	Prodcut Weight	Description	
906001-4	1#	NPT Vented Cap, 2"	Confession Confession 2

ATT-200

Transfer Mounting Bracket

