GAS ENGINE ADAPTERS

PEM-F FLANGE


Pump Gas Engine Adapters (Bell Housings) are designed to assure proper shaft alignment between the gasoline engine and your hydraulic pump. They also reduce assembly cost over using a foot mounting bracket or riser.


Standard Features:


- · Light weight High strength
- Drive coupling accessibility
- Proper shaft alignment assured
- Gas Engine Adapters are designed to be used with gas engines with horizontal shafts only.

Standard Material:


Cast Aluminum










Adapter 6049 6061







NOTE: All dimensions are inches.



Gas Engine Adapter - PEM-F Flange (inches)								
Part No.	Pump Type	Pump Mounting Flange	MAX Coupling Dia	XAJ Bolt Circle	XAK Pump Pilot	XBF Mounting Holes (NC)	M Face to Face	Inside Clearance
6048	USAF 4F17	4 Bolt	2.63	2.84	1.78	5/16-18	4.50	3.38
6049	SAE AA	2 Bolt	2.81	3.25	2.00	3/8-16	4.50	3.38
6061	SAE A	2 Bolt	2.81	4.19	3.25	3/8-16	4.69	3.38

Dimensions and specifications are subject to change without notice. Not all items are Made-To-Stock, contact us for availability.

sales@ldi-industries.com

GAS ENGINE ADAPTERS

GAS ENGINE MOUNTING FLANGE INFORMATION

Standard Features:

- Decrease assembly time bolt mount to side of gas engine
- Made of lightweight but strong cast aluminum
- Proper shaft alignment assured
- Reduced cost no need for foot brackets, shims or risers
- Provide a clean, neat appearance for your finished product
- Gas Engine Adapters are designed to be used with gas engines with horizontal shafts only.

Easy Assembly Pump to Gas Engine:


- Place coupling half for engine on engine shaft and lightly tighten set screw
- Mount pump to pump end of gas engine adapter
- Place coupling half for pump on pump shaft and lightly tighten set screw
- Position coupling insert Bolt gas engine adapter with pump installed to the face of the gas engine
- Adjust coupling thru access opening Thoroughly tighten set screws and mounting bolts

PEM-F FLANGE *Dimensions to be furnished by custome 45° 2.56 1.28 1.625 DIA.

BOLT CIRCLE
MOUNTING FLANGE PER SAE J609a

3.625 DIA.

PEM-H FLANGE *Dimensions to be furnished by custor





PEM-G FLANGE

*Dimensions to be furnished by custome



*Dimensions to be furnished by customer





NOTE: All dimensions are inches

sales@ldi-industries.com www.ldi-industries.com